



Mobil Super™ 3000 X1 5W-40
Mobil Passenger-Vehicle-Lube , Romania
Premium Full Synthetic Passenger Vehicle Motor Oil

Product Description

Mobil Super™ 3000 x1 5W-40 is a fully synthetic engine oil that provides long engine life for many types and ages of vehicles with enhanced protection over a wide temperature range.

Features and Benefits

Mobil Super 3000 products are industry proven so you can trust you will get the protection you want from your vehicle. Mobil Super 3000 x1 5W-40 provides:

- Enhanced high temperature protection
- Enhanced cold start-up protection
- Enhanced engine cleanliness and sludge prevention
- Enhanced wear protection

Applications

Mobil Super 3000 products are formulated to give you confidence of protection beyond that of conventional or semi-synthetic oils. ExxonMobil recommends Mobil Super 3000 x1 5W-40 if you regularly experience demanding conditions where it can help combat the damage caused by frequent high engine stress:

- Passenger cars, SUV's, light trucks and vans
- Gasoline and Diesel engines, without particulate filters (DPF)
- High performance engines with turbo-chargers and direct injection
- Highway cruising and stop and go city driving
- Normal to frequently severe operating conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

| This product has the following approvals: |
|---|
| Porsche A40 |
| PSA B71 2296 |
| RENAULT RN0700 |
| RENAULT RN0710 |
| VW 502 00 |
| VW 505 00 |

This product has the following approvals:

MB-Approval 229.3

This product is recommended for use in applications requiring:

API CF

FIAT 9.55535-G2

This product meets or exceeds the requirements of:

ACEA A3/B4

API SL

API SM

API SN

Fiat 9.55535-M2

Properties and Specifications

| Property | |
|--|-----------|
| Grade | SAE 5W-40 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 13.2 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 79 |
| Density @ 15.6 C, g/ml, ASTM D4052 | 0.847 |
| Pour Point, °C, ASTM D97 | -39 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 236 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2025

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO
ENERGY

© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved