

Lubricants - Agricultural

Version: **EEE/37**

Valvoline™ STOU SAE 15W-40

STOU is a premium multi-functional oil specially formulated for use in agricultural equipment, engines, transmissions, and differentials with wet brake system and integrated hydraulic system. The product can be used for total tractor lubrication and is approved by many tractor manufacturers.

Performance levels

ISO L-E/C/H
API: CF-4, CE/SF
API: GL-4
Allison C3, C4
Caterpillar TO-2
Ford M2C 159B, C
Ford M2C 86B, C, 134 D,
Ford NH 82009201, 2, 3
J.I Case/Case Int: MS-1204, 6, 7, 9
CNH MAT 3525, 3526
John Deere JDM J27, J20C, J20D
MF M1139, M1144, M1145
ZF TE-ML 06A, B, C, R, 07B

Applications

Total tractor lubrication, engine, gearbox, differential, hydraulic system.

STOU SAE 15W-40 is high quality universal oil meeting requirements for the lubrication of diesel engines with and without turbocharging, gearboxes, transmissions, differentials and gears, hydraulic systems and wet brakes of tractors.

STOU SAE 15W-40 can be used as engine oil for transportation vehicles and other equipment and in that way it fulfills its multifunctional properties.

Features & Benefits

Wear protection

Super Tractor Oil Universal is specially formulated for agricultural use, adjusted to different circumstances like low speed/high torque etc. The carefully chosen base oils and additive system form a protective oil film for all the tractor components.

Tractor component cleanliness

Detergent and dispersant additives keep the engine, gearbox, differential, and hydraulic system clean and in good condition. The oil is resistant against moist and oxidation.

Multi-Purpose

Super Tractor Oil Universal can be used for the engine, the gearbox, the differential, and the hydraulic system. A real multipurpose use. An extra advantage is 1 oil for the whole tractor and less storage; no miss-applications.

Break Down resistance

Thermal and Oxidation stable oil film. Special Extreme Pressure additives protect the tractor components against break down.

Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineeurope.com

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

STOU	
SAE Viscosity Grade	15W-40
Viscosity, mm²/s @ 100 °C. ASTM D-445	14,4
Viscosity, mm²/s @ 40 °C. ASTM D-445	111
Viscosity Index ASTM D-2270	130
Viscosity, mPa.s -20°C. ASTM D-5293	<7000
TBN, mg KOH/g ASTM D-2896	≥9,6
Pour Point, °C ASTM D-97	-33
Specific Gravity @ 15.6°C. ASTM D-1298	0,888
Flash Point, COC, °C. ASTM D-92	>200

This information only applies to products manufactured by:

Ellis Enterprises East doo Kruševac,
Affiliate of Valvoline
Mike Stojanovića 15, 37000 Kruševac, Serbia
Registration nr: 21368997 / TIN: 110618744

™ Trademark of Valvoline, registered in various countries

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises East doo Kruševac and its affiliates assume legal responsibility.

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <https://sds.valvoline.com/>

Protect the environment

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces –