

## Description

It is the synthetic lubricant oil for high-performance 4-stroke engines, and it is suitable for off-road bikes in their very varied disciplines, such as trial, enduro and motocross. It provides maximum protection for engines in extreme conditions, when they are subjected to high temperatures or during long operating periods. It guarantees maximum performance in or out of competition thanks to its contained evaporation and the exclusive formulation ensuring engine life.

## Properties

- Formulated to provide total protection, with excellent protection against wear and engine cleanliness guaranteed.
- Its viscosimetric properties help start the engine in cold temperatures and aid lubrication at any temperature.
- Provides good friction on clutch discs, preventing slippage and premature wear in joint engine and transmission (wet clutch) lubrication systems
- Specially developed for use in conditions of high rotations, demonstrating superior capacity in off-road use.

## Quality levels, approvals and recommendations

- API SN
- JASO T 903:2016 MA2\*
- \*Formal approval

## Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			10W-40
Density at 15 °C	g/cm3	ASTM D 4052	0,85
Viscosity at 100 °C	cSt	ASTM D 445	14
Viscosity at -40 °C	cSt	ASTM D 445	89
Viscosity at -25 °C	cP	ASTM D 5293	7000 maximum
Viscosity index	-	ASTM D 2270	160
Flash point, open cup	°C	ASTM D 92	244
Pour point	°C	ASTM D 97	-39
T.B.N.	mg KOH/g	ASTM D 2896	7
Sulphated ashes	% weight	ASTM D 874	0,8
Bosch injector shear at 100 °C	cSt	CEC-L014-93	12 mín

The above mentioned characteristics are typical values and should not be considered product specifications.