

SAFETY DATA SHEET



Castrol Outboard 2T

Section 1. Identification

GHS product identifier Castrol Outboard 2T

Product code 456657-ID01

SDS no. 456657

Relevant identified uses of the substance or mixture and uses advised against

**Use of the substance/
mixture** Small engine oil.
For specific application advice see appropriate Technical Data Sheet or consult our company representative.

Manufacturer

Supplier Castrol Australia Pty Ltd
Level 17, 717 Bourke Street
Docklands, Victoria 3008
ABN 87 008 459 407
www.castrol.com.au

Tel: +61 (03) 9268 4111

**EMERGENCY TELEPHONE
NUMBER** +61 2801 44558 (or 1800 14 14 74 within Australia)

**OTHER PRODUCT
INFORMATION** Technical Advice Helpline Number: 1300 557 998

Section 2. Hazard(s) identification

**Classification of the
substance or mixture** Not classified.

GHS label elements

Signal word No signal word.

Hazard statements No known significant effects or critical hazards.

Precautionary statements

Prevention Not applicable.

Response Not applicable.

Storage Not applicable.

Disposal Not applicable.

**Supplemental label
elements** Not applicable.

**Other hazards which do not
result in classification** Defatting to the skin.
NOTE: Product diluted with petrol must be handled with the same precautions used for petrol. Before mixing, the Safety Data Sheet for petrol should be consulted for any precautionary measures necessary.

Section 3. Composition and ingredient information

Substance/mixture Mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Product name Castrol Outboard 2T

Product code 456657-ID01 **Page:** 1/10

Version 1 **Date of issue** 9/4/2023

Format Australia
(Australia)

Language ENGLISH
(ENGLISH)

Section 3. Composition and ingredient information

Ingredient name	% (w/w)	CAS number
Distillates (petroleum), solvent-dewaxed heavy paraffinic	≥30 - ≤60	64742-65-0
Distillates (petroleum), hydrotreated heavy paraffinic	≥10 - ≤30	64742-54-7
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	≥10 - ≤30	64742-47-8
Distillates (petroleum), solvent-dewaxed light paraffinic	≤3	64742-56-9
white mineral oil, petroleum	≤3	8042-47-5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

The total concentration of ingredients in this product, reported or not in this section, is 100%.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
Skin contact	Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects.
Specific treatments	No specific treatment.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training.

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media	In case of fire, use water fog, alcohol resistant foam, dry chemical or carbon dioxide extinguisher or spray.
Unsuitable extinguishing media	Do not use water jet.

Specific hazards arising from the chemical

In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products

Combustion products may include the following:
carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)

Special protective actions for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Product name	Castrol Outboard 2T	Product code	456657-ID01	Page:	2/10
Version	1	Date of issue	9/4/2023	Format	Australia
				(Australia)	
				Language	ENGLISH
				(ENGLISH)	

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). NOTE: Product diluted with petrol must be handled with the same precautions used for petrol. Before mixing, the Safety Data Sheet for petrol should be consulted for any precautionary measures necessary.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Not suitable

Prolonged exposure to elevated temperature

Section 8. Exposure controls and personal protection

Control parameters

Occupational exposure limits

Section 8. Exposure controls and personal protection

Ingredient name	Exposure limits
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Safe Work Australia (Australia). [Oil mist, refined mineral] TWA: 5 mg/m ³ 8 hours. Issued/Revised: 5/1995 Form: Mist
Distillates (petroleum), hydrotreated heavy paraffinic	Safe Work Australia (Australia). [Oil mist, refined mineral] TWA: 5 mg/m ³ 8 hours. Issued/Revised: 5/1995 Form: Mist
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	ACGIH TLV (United States). [Kerosene] Absorbed through skin. TWA: 200 mg/m ³ , (as total hydrocarbon vapor) 8 hours. Issued/Revised: 1/2003
Distillates (petroleum), solvent-dewaxed light paraffinic	Safe Work Australia (Australia). [Oil mist, refined mineral] TWA: 5 mg/m ³ 8 hours. Issued/Revised: 5/1995 Form: Mist
white mineral oil, petroleum	Safe Work Australia (Australia). [Oil mist, refined mineral] TWA: 5 mg/m ³ 8 hours. Issued/Revised: 5/1995 Form: Mist

Biological exposure indices

No exposure indices known.

Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety glasses with side shields.

Skin protection

Section 8. Exposure controls and personal protection

Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Skin protection

Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Refer to standards:

Respiratory protection: AS/NZS 1715 and AS/NZS 1716
Gloves: AS/NZS 2161.1
Eye protection: AS/NZS 1336 and AS/NZS 1337

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state

Liquid.

Colour

Green. [Light]

Odour

Not available.

Odour threshold

Not available.

pH

Not applicable.

Melting point

Not available.

Boiling point, initial boiling point, and boiling range

Not available.

Flash point

Closed cup: 100°C (212°F) [Pensky-Martens ASTM D 93 typical value]

Evaporation rate

Not available.

Not applicable. Based on - Physical state

Lower and upper explosion limit/flammability limit

Not available.

Vapour pressure

Section 9. Physical and chemical properties

Ingredient name	Vapour Pressure at 20 °C			Vapour pressure at 50 °C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Distillates (petroleum), solvent-dewaxed heavy paraffinic	<0.08	<0.011	ASTM D 5191			
Distillates (petroleum), hydrotreated heavy paraffinic	<0.08	<0.011	ASTM D 5191			
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	0.23 to 0.45	0.031 to 0.06				
Polybutene (Isobutylene/butene copolymer)	<0.75	<0.1				
white mineral oil, petroleum	0.08	0.011	OECD 104			

Relative vapour density

Not available.

Relative density

Not available.

Density

<1000 kg/m³ (<1 g/cm³) at 15 °C

Solubility(ies)

Media	Result
water	Not soluble

Solubility in water

Not available.

Partition coefficient: n-octanol/water

Not applicable.

Auto-ignition temperature

Ingredient name	°C	°F	Method
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	>220	>428	
Polybutene (Isobutylene/butene copolymer)	215	419	EU A.15
white mineral oil, petroleum	325 to 355	617 to 671	ASTM E 659

Decomposition temperature

Not available.

Viscosity

Kinematic: 51.9 mm²/s (51.9 cSt) at 40 °C
Kinematic: 8.62 mm²/s (8.62 cSt) at 100 °C

Particle characteristics

Median particle size

Not applicable.

Section 10. Stability and reactivity

Reactivity

No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.

Chemical stability

The product is stable.

Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.
Under normal conditions of storage and use, hazardous polymerisation will not occur.

Conditions to avoid

Avoid all possible sources of ignition (spark or flame).

Incompatible materials

Reactive or incompatible with the following materials: oxidising materials.

Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Product name Castrol Outboard 2T

Product code 456657-ID01 **Page: 6/10**

Version 1 **Date of issue** 9/4/2023

Format Australia
(Australia)

Language ENGLISH
(ENGLISH)

Section 11. Toxicological information

Information on toxicological effects

Aspiration hazard

Name

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Distillates (petroleum), solvent-dewaxed light paraffinic white mineral oil, petroleum

Result

ASPIRATION HAZARD - Category 1

ASPIRATION HAZARD - Category 1

ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

Routes of entry anticipated: Dermal, Inhalation, Eyes.

Potential acute health effects

Eye contact

No known significant effects or critical hazards.

Inhalation

Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.

Skin contact

Defatting to the skin. May cause skin dryness and irritation.

Ingestion

No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact

No specific data.

Inhalation

No specific data.

Skin contact

Adverse symptoms may include the following:
irritation
dryness
cracking

Ingestion

No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact

Potential risk of transient stinging or redness if accidental eye contact occurs.

Inhalation

Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.

Skin contact

Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Ingestion

Ingestion of large quantities may cause nausea and diarrhoea.

General

No known significant effects or critical hazards.

Carcinogenicity

No known significant effects or critical hazards.

Mutagenicity

No known significant effects or critical hazards.

Teratogenicity

No known significant effects or critical hazards.

Developmental effects

No known significant effects or critical hazards.

Fertility effects

No known significant effects or critical hazards.

Section 12. Ecological information

Persistence and degradability

Expected to be biodegradable.

Bioaccumulative potential

Product name Castrol Outboard 2T

Product code 456657-ID01

Page: 7/10

Version 1 **Date of issue** 9/4/2023

Format Australia

Language ENGLISH

(Australia)

(ENGLISH)

Section 12. Ecological information

This product is not expected to bioaccumulate through food chains in the environment.

Mobility in soil

Soil/water partition
coefficient (K_{oc})

Not available.

Mobility

Spillages may penetrate the soil causing ground water contamination.

Other ecological information

Spills may form a film on water surfaces causing physical damage to organisms.
Oxygen transfer could also be impaired.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Special Precautions for Landfill or Incineration

No additional special precautions identified.

Section 14. Transport information

	ADG	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Additional information	-	-	-

Special precautions for user

Not available.

Section 15. Regulatory information

Standard for the Uniform Scheduling of Medicines and Poisons

Not regulated.

Model Work Health and Safety Regulations - Scheduled Substances

No listed substance

Montreal Protocol

Product name Castrol Outboard 2T

Product code 456657-ID01

Page: 8/10

Version 1 Date of issue 9/4/2023

Format Australia

Language ENGLISH

(Australia)

(ENGLISH)

Section 15. Regulatory information

Not listed.

[Stockholm Convention on Persistent Organic Pollutants](#)

Not listed.

[Rotterdam Convention on Prior Informed Consent \(PIC\)](#)

Not listed.

[International lists](#)

[National inventory](#)

[REACH Status](#)

For the REACH status of this product please consult your company contact, as identified in Section 1.

[Australia inventory \(AIC\)](#)

All components are listed or exempted.

[Canada inventory](#)

All components are listed or exempted.

[China inventory \(IECSC\)](#)

All components are listed or exempted.

[Japan inventory \(CSCL\)](#)

All components are listed or exempted.

[Korea inventory \(KECI\)](#)

All components are listed or exempted.

[Philippines inventory \(PICCS\)](#)

All components are listed or exempted.

[Taiwan Chemical Substances Inventory \(TCSI\)](#)

All components are listed or exempted.

[United States inventory \(TSCA 8b\)](#)

Not determined.

Section 16. Any other relevant information

[History](#)

[Date of printing](#) 9/4/2023

[Date of issue/Date of revision](#) 9/4/2023

[Date of previous issue](#) No previous validation

[Version](#) 1

[Prepared by](#) Product Stewardship Group

[Key to abbreviations](#)

ADG = Australian Dangerous Goods

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

NOHSC = National Occupational Health and Safety Commission

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]

STEL = Short term exposure limit

SUSMP = Standard Uniform Schedule of Medicine and Poisons

UN = United Nations

TWA = Time weighted average

VOC = Volatile Organic Compound

SADT = Self-Accelerating Decomposition Temperature

Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1,

[Product name](#) Castrol Outboard 2T

[Product code](#) 456657-ID01 **Page: 9/10**

[Version](#) 1 [Date of issue](#) 9/4/2023

[Format](#) Australia

[Language](#) ENGLISH

(Australia)

(ENGLISH)

Section 16. Any other relevant information

64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0,
72623-87-1

Procedure used to derive the classification

Classification	Justification
Not classified.	

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name Castrol Outboard 2T

Product code 456657-ID01 **Page: 10/10**

Version 1 **Date of issue** 9/4/2023

Format Australia
(Australia)

Language ENGLISH
(ENGLISH)