



Product Data

Castrol Outboard 4T

Enhanced Piston Cleanliness For 4T high performance outboard engines.

Description

Castrol Outboard 4T is a high performance lubricant that provides excellent protection over the wide range of operating conditions typical of outboard engines, ranging from high speed cruising to extended periods at idle.

Application

Castrol Outboard 4T has been designed for all 4 stroke outboard engines from major Japanese and American manufacturers.

Advantages

- Enhanced piston cleanliness and reduced oil consumption.
- Excellent low temperature wear control for effective valvetrain protection.
- High resistance to viscosity losses allowing a thick oil film to be maintained over time, even in the presence of high levels of fuel dilution.
- Good anticorrosion properties for safe protection during winter storage.

Typical Characteristics

Name	Method	Units	Castrol Outboard 4T
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	74.4
Pour Point	ASTM D97	°C	-42
Flash Point, PMCC	ASTM D93	°C	220
Density @ 15C, Relative	ASTM D4052	g/ml	0.860
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	11.4
Viscosity Index	ASTM D2270	None	145

Performance

API SL/CF

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Outboard 4T

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW
Orders/Enquiries: 0345 6008125 Technical Enquiries: 0345 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353
www.castrol.com/uk